







RUMBLE STRIP DETAILS




TYPE A
CYLINDER RUMBLE STRIP
(BICYCLE TRAVEL PROHIBITED)



TYPE B
CYLINDER RUMBLE STRIP
(BICYCLE TRAVEL PERMITTED)



TYPE C
CONTINUOUS SINUSOIDAL
RUMBLE STRIP



- NOTES:
1. NOT TO SCALE. SOME LINE WORK EXAGGERATED FOR CLARITY.
 2. SEE PLANS FOR LOCATION(S) AND START AND END STATIONS FOR ALL RUMBLE STRIP INSTALLATIONS.
 3. HIGH POINT OF SINUSOIDAL RUMBLE STRIP LOCATED $\frac{1}{16}$ " BELOW PAVEMENT SURFACE.

DESIGN OF CURVE PROFILE FOR SINUSOIDAL RUMBLE STRIP									
POINT	A	B	C	D	E	F	G	H	I
DEPTH FROM PAVEMENT SURFACE (IN.)	$\frac{1}{16}$	$\frac{1}{8}$	$\frac{7}{32}$	$\frac{11}{32}$	$\frac{3}{8}$	$\frac{11}{32}$	$\frac{7}{32}$	$\frac{1}{8}$	$\frac{1}{16}$
DISTANCE FROM HIGH POINT "A" (IN.)	0	1.75	3.5	5.25	7	8.75	10.5	12.25	14



TRAFFIC & SAFETY STANDARDS
SECTION 860

RUMBLE STRIP DETAILS

D-TE OF ISSUE
2020

DR- ING NUMBER
XXX.X.X